

October 24, 2005

Response 02, ISS1.002
Application No. 10/811,550**Listing of Claims**

1. (currently amended) A flue liner insert comprising four individual substantially identical components of sheet material, each component having a cross section that is generally L-shaped with a beveled corner, the components together forming a vertical flue passage of substantially constant cross sectional area throughout the length of said vertical flue passage, each component comprising adjustable fastening means such that each component is independently adjustable in position with respect to the other components.
2. (original) The flue liner insert of claim 1, wherein the flue liner insert further comprises one or more placement tabs extending at a predetermined height of the flue liner insert.
3. (original) The flue liner insert of claim 2, wherein the upper portion of the flue liner insert has at least one ventilation hole therein.
4. (original) A method of using a flue liner insert of claim 3 to extend and terminate a chimney having an existing flue tile at its top, comprising:
 - a) Inserting the flue liner insert into the existing flue tile at a depth predetermined by the location of a placement tab; and
 - b) Attaching a chimney cap to the upper end of the flue liner insert.
5. (original) A method of using a flue liner insert of claim 2 to extend a chimney having an existing flue tile at its top, comprising:
 - a) Inserting the flue liner insert into the existing flue tile at a depth predetermined by the location of a placement tab; and
 - b) Placing an extending flue tile over the flue liner insert such that it is directly or indirectly supported by the existing flue tile.
- 6-17. (canceled)

October 24, 2005

Response 02, ISS1.002
Application No. 10/811,550

18. (new) A method of using a flue liner insert of claim 1 to extend a chimney having an existing flue tile at its top, comprising:

- a) Inserting the flue liner insert into an existing flue tile;
- b) Placing a metal shroud around the exterior of the flue liner insert; and
- c) Fastening the metal shroud to the flue liner insert.

19. (new) A method of using a flue liner insert of claim 1 to extend a chimney having an existing flue tile at its top, comprising:

- a) Inserting the flue liner insert into an existing flue tile; and
- b) Placing a chimney pot over the flue liner insert.